



# ABB B23 Three Phase Direct Part Code: AB065TD

Advanced compact DIN-rail meter with an easy to read back lighted display. The meter is intended for use in commercial or residential buildings etc. The meter can be used in 3 or 4 wire systems. The meter has several instrumentation values, 26 possible alarms and event logs. Three phase direct connected for active energy. One output for pulses or alarm etc. Accuracy class 1.0 (or B for MID meters). The meter is IEC approved + MID approved and verified.



sycous.com 💪 +44 (0) 113 3604 776 🖂 info@sycous.com 🛛 New York House, 1 Harper Street, Leeds, LS2 7EA

#### **Technical Datasheet** . . . . . . . . . . . . . . .

ABB B23 Three Phase Direct

AB065TD



Part Code	Name	Phase	Connection	Output
AB065TD	ABB Three Phase Direct Electricity Meter 65A - Pul	THREE	DIRECT	PULSE
AB066TD	ABB Three Phase Direct Electricity Meter 65A - RS4	THREE	DIRECT	RS485
AB083TD	ABB Three Phase Direct Electricity Meter 65A - Mbu	THREE	DIRECT	MBUS/ PULSE

Product Net Width	70 mm
Product Net Height	26.5 mm
Product Net Depth / Length	65 mm
Product Net Weight	0.31 kg
Container Information	

Package Level 1 Units	1 piece	-
Package Level 1 Width	100 mm	
Package Level 1 Height	68 mm	
Package Level 1 Depth / Length	94 mm	
Package Level 1 Gross Weight	0.39 kg	
Package Level 1 EAN	7392696001632	
Environmental		

Ambient Air Temperature	Operation -40 +70 °C	
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment	
Additional Information		
Accuracy	Active Energy Class ±1% (or B for MID meters).	
Communication Interface	Other	
Communication	Pulse output / IR port	

### Customer Billing **Services**

Meter Data Management

**Billing Solutions** 

PAYG Management

Online Account Management

sycous.com

sycous.com

+44 (0) 113 3604 776 🛛 info@sycous.com 🛛 🖗 New York House, 1 Harper Street, Leeds, LS2 7EA

#### Technical Datasheet . . . . . . . . . . . . . . . .

ABB B23 Three Phase Direct

AB065TD



Current Rating	65 A
Degree of Protection	IP20
Enclosure Material	Plastic
Frequency (f)	50/60 Hz
Function	Electricity meter
Meter Type	Direct connected
Mounting Type	DIN rail
Number of Phases	3
Product Main Type	B23
Product Name	Electricity Meter
Rated Current (In)	65 A
Rated Voltage (Ur)	(Un) N-L 220 240 V (Un) L-L 380 415 V
RoHS Date	2012-36
Standards	EN 50470-1
Sub-Function	Steel
Certificates and Declarations (Doc	ument Number)
Data Sheet, Technical Information	2CMC485003M0201
Declaration of Conformity - CE	2CMC485001D0001
Environmental Information	2CMC485003D0001
Instructions and Manuals	2CMC485019M0201

## Data

### Collection

Wired Networks

Wireless Networks

IoT Technologies

MBus & Pulse for any network

#### sycous.com

Classifications			
ETIM 4	EC001506 - Electronic kilowatt-hour meter		
ETIM 5	EC001506 - Kilowatt-hour meter		
ETIM 6	EC001506 - Kilowatt-hour meter		
ETIM 7	EC001506 - Kilowatt-hour meter		
Object Classification Code	Ρ		
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)		

2CMC485006

sycous.com

**RoHS** Information

+44 (0) 113 3604 776 🛛 info@sycous.com 🛛 🖗 New York House, 1 Harper Street, Leeds, LS2 7EA