



ABB A41 Single Phase Direct

Part Code: AB080SD

Advanced DIN-rail meter with a large and easy to read back lighted pixel-oriented display. The meter is intended for use in the industry, commercial buildings etc. The meter can be used in 3 or 4 wire systems with a wide voltage range. The meter has several instrumentation values, 25 possible alarms and event logs. Single phase direct connected or active energy. One output for pulses or alarm etc. Accuracy class 1.0 (or B for MID meters). The meters is IEC approved + MID approved and verified.



svcous.com

ABB A41 Single Phase Direct AB080SD



Dimensions	
Product Net Width	70 mm
Product Net Height	26.5 mm
Product Net Depth /Length	65 mm
Product Net Weight	0.236 kg
Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	100 mm
Package Level 1 Height	68 mm
Package Level 1 Depth /Length	94 mm
Package Level 1 Gross Weight	0.308 kg
Package Level 1 EAN	7392696705547
Environmental	
Ambient Air Temperature	Operation -40 +70 °C
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
	and amendment
Additional Information	and amendment
Additional Information	Active Energy Class ±1% (or B for MID meters).
Accuracy	Active Energy Class ±1% (or B for MID meters).
Accuracy Communication Interface	Active Energy Class ±1% (or B for MID meters). Other
Accuracy Communication Interface Communication	Active Energy Class ±1% (or B for MID meters). Other Pulse output / IR port
Accuracy Communication Interface Communication Connecting Capacity Main Circuit	Active Energy Class ±1% (or B for MID meters). Other Pulse output / IR port 1 25 mm
Accuracy Communication Interface Communication Connecting Capacity Main Circuit Current Rating	Active Energy Class ±1% (or B for MID meters). Other Pulse output / IR port 1 25 mm 80 A
Accuracy Communication Interface Communication Connecting Capacity Main Circuit Current Rating Degree of Protection	Active Energy Class ±1% (or B for MID meters). Other Pulse output / IR port 1 25 mm 80 A IP20
Accuracy Communication Interface Communication Connecting Capacity Main Circuit Current Rating Degree of Protection Enclosure Material	Active Energy Class ±1% (or B for MID meters). Other Pulse output / IR port 1 25 mm 80 A IP20 Plastic
Accuracy Communication Interface Communication Connecting Capacity Main Circuit Current Rating Degree of Protection Enclosure Material Frequency (f)	Active Energy Class ±1% (or B for MID meters). Other Pulse output / IR port 1 25 mm 80 A IP20 Plastic 50 60 Hz
Accuracy Communication Interface Communication Connecting Capacity Main Circuit Current Rating Degree of Protection Enclosure Material Frequency (f) Function	Active Energy Class ±1% (or B for MID meters). Other Pulse output / IR port 1 25 mm 80 A IP20 Plastic 50 60 Hz Electricity meter
Accuracy Communication Interface Communication Connecting Capacity Main Circuit Current Rating Degree of Protection Enclosure Material Frequency (f) Function Meter Type	Active Energy Class ±1% (or B for MID meters). Other Pulse output / IR port 1 25 mm 80 A IP20 Plastic 50 60 Hz Electricity meter Direct connected
Accuracy Communication Interface Communication Connecting Capacity Main Circuit Current Rating Degree of Protection Enclosure Material Frequency (f) Function Meter Type Mounting Type	Active Energy Class ±1% (or B for MID meters). Other Pulse output / IR port 1 25 mm 80 A IP20 Plastic 50 60 Hz Electricity meter Direct connected DIN rail



Managed **Services**

Meter Data Management

Billing Solutions

PAYG Management

Online Account Management

sycous.com

ABB A41 Single Phase Direct AB080SD



Rated Current (In)	80 A
Rated Voltage (Ur)	(Un) N-L 57,7 288 V
RoHS Date	2011-44
Standards	EN 50470-1
Sub-Function	Steel

Certificates and Declarations (Document Number)		
Data Sheet, Technical Information	2CMC484002M0201	
Declaration of Conformity - CE	2CMC484003D0001	
Environmental Information	2CMC484004D0001	
Instructions and Manuals	2CMC484010M4901	
RoHS Information	2CMC484006	

Classifications	
ETIM 4	EC001506 - Electronic kilowatt-hour meter
ETIM 5	EC001506 - Kilowatt-hour meter
ETIM 6	EC001506 - Kilowatt-hour meter
ETIM 7	EC001506 - Kilowatt-hour meter
Object Classification Code	Р
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)



Data Collection

Wired Networks

Wireless Networks

IoT Technologies

MBus & Pulse for any network

sycous.com